



## TP-Link Archer C80 trådløs router Gigabit Ethernet Dual-band (2,4 GHz / 5 GHz) Sort

Mærke : TP-Link

Produktkode: ARCHER C80

Produkt navn : Archer C80

TP-Link Archer C80. WAN forbindelsestype: RJ-45. Wi-Fi-bånd: Dual-band (2,4 GHz / 5 GHz), Bedste Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN dataoverførselshastighed (maks): 1300 Mbit/s. Ethernet LAN-grænsefladetype: Gigabit Ethernet, Ethernet LAN-datahastigheder: 10,100,1000 Mbit/s, Kabelteknologi: 10/100/1000Base-T(X). Sikkerhedsalgoritmer: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Produkttype: Bordplade router, Produktfarve: Sort, LED-indikatorer: LAN, Strøm, Status, WLAN, WPS



<b>WAN-forbindelse</b>		<b>Protokoller</b>	
Ethernet WAN *	✓	Universal Plug and Play (UPnP)	✓
SIM-kort slot *	✗	<b>Design</b>	
WAN forbindelsestype	RJ-45	Produktfarve	Sort
<b>Trådløse LAN funktioner</b>		Kan monteres på væggen	✓
Wi-Fi-bånd *	Dual-band (2,4 GHz / 5 GHz)	LED-indikatorer	LAN, Strøm, Status, WLAN, WPS
Bedste Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Tænd-/slukkontakt	✓
WLAN dataoverførselshastighed (maks) *	1300 Mbit/s	Produkttype *	Bordplade router
Wi-Fi-standarder	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)	<b>Emballage indhold</b>	
WLAN dataoverførselshastighed (første bånd)	1300 Mbit/s	Kabler inkluderet	Vekselstrøm, LAN (RJ-45)
<b>Netværk</b>		AC-adapter inkluderet	✓
Ethernet LAN *	✓	Hurtig installationsvejledning	✓
Ethernet LAN-grænsefladetype *	Gigabit Ethernet	<b>Antenne</b>	
Ethernet LAN-datahastigheder	10,100,1000 Mbit/s	Antennedesign *	Ekstern
Kabelteknologi	10/100/1000Base-T(X)	Antenner, antal	4
Netværksstandarder	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Aftagelig (e) antenne (r)	✗
Portvideresendelse	✓	Overfører strøm	CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz), FCC:<30dBm(2.4 GHz & 5 GHz)
Dynamisk DNS (DDNS)	✓	<b>Strømstyring</b>	
<b>Porte &amp; Grænseflader</b>		Strømkilde type *	DC
Ethernet LAN-porte (RJ-45) *	5	Udgangsspænding	12 V
USB-port *	✗	<b>Driftsbetingelser</b>	
Hukommelseskortstik	✗	Driftstemperatur (T-T)	0 - 40 °C
DC-in-stik	✓	Opbevaringstemperatur (T-T)	-40 - 70 °C
<b>Administrationsfunktioner</b>		Relativ luftfugtighed ved drift (H-H)	10 - 90%
Knap til nulstilling	✓	Relativ luftfugtighed ved opbevaring (H-H)	5 - 90%
WPS tryknap	✓	<b>Systemkrav</b>	
		Understøttet browser	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0

Sikkerhed		Systemkrav	
Sikkerhedsalgoritmer	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK		Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Firewall	✓		
Gæstegang	✓		
Adgangskontrolliste (ACL)	✓		
Stateful Packet Inspection (SPI)	✓		
Filtrering af MAC-adresser	✓		
Understøttelse af DMZ	✓		
Protokoller			
DHCP-klient	✓		
DHCP-server	✓		
		Understøttede Windows-operativsystemer	
		Understøttede Linux-operativsystemer	✓
		Understøttede Mac-operativsystemer	MacOS
		Mac kompatibilitet	✓
		Emballeringsdata	
		Pakkebredde	350 mm
		Pakkedybde	240 mm
		Pakkehøjde	82 mm
		Pakkevægt	800 g



6935364088873

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-OCT-2024. Prints or copies of Information are only valid on the printed Publication date