



TP-Link Archer TX50E WLAN / Bluetooth 2402 Mbit/s

Mærke : TP-Link

Produktkode: ARCHER TX50E

Produktnavn : Archer TX50E

TP-Link Archer TX50E. Forbindelsesteknologi: Trådløs, Værtsgrænseflade: PCI Express, Grænseflade: WLAN / Bluetooth. Maksimal dataoverførselshastighed: 2402 Mbit/s, Bedste Wi-Fi standard: Wi-Fi 6 (802.11ax), Wi-Fi-bånd: Dual-band (2,4 GHz / 5 GHz). Produktfarve: Sort, Metallic



Porte & Grænseflader		Systemkrav	
Forbindelsesteknologi *	Trådløs	Understøttede Windows-operativsystemer	Windows 10 Education x64, Windows 10 Enterprise x64, Windows 10 Home x64, Windows 10 Pro x64, Windows 10 x64
Værtsgrænseflade *	PCI Express		
Grænseflade *	WLAN / Bluetooth		
Netværk		Driftsbetingelser	
Maksimal dataoverførselshastighed *	2402 Mbit/s	Driftstemperatur (T-T)	0 - 40 °C
Netværksstandarder *	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Opbevaringstemperatur (T-T)	-40 - 70 °C
		Relativ luftfugtighed ved drift (H-H)	10 - 90%
Wi-Fi	✓	Relativ luftfugtighed ved opbevaring (H-H)	5 - 90%
Wi-Fi-bånd	Dual-band (2,4 GHz / 5 GHz)	Bæredygtighed	
Frekvensområde	2,4 - 5 GHz	Overholdelse af bæredygtighed	✓
Bedste Wi-Fi standard	Wi-Fi 6 (802.11ax)	Vægt & størrelser	
Wi-Fi-standarder	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Bredde	95,2 mm
		Dybde	120,8 mm
		Højde	21,5 mm
Understøttede WLAN-dataoverførselshastigheder	54,300,574,1733,2402 Mbit/s	Emballeringsdata	
Modulation	16-QAM, 64-QAM, 256-QAM, DBPSK, DQPSK, OFDM	Pakkebredde	200 mm
Sikkerhedsalgoritmer	64-bit WEP, 128-bit WEP, 802.1x RADIUS, WPA, WPA-PSK, WPA2, WPA2-PSK, WPA3	Pakkedybde	150 mm
		Pakkehøjde	39 mm
Bluetooth	✓	Pakkevægt	270 g
Bluetooth-version	5.0	Emballage indhold	
Design		Monteringsbeslag inkluderet	✓
Produktfarve	Sort, Metallic	Ressource CD	✓
Intern *	✗	Bluetooth header kabel	✓
Antenne	✓	Hurtig installationsvejledning	✓
Antennedesign	Ekstern		

Design		Tekniske detaljer	
Niveau for antennestyrke (maks.)	5 dBi	Compliance-certifikater	CE, Federal Communications Commission (FCC), RoHS
Sendeeffekt (CE)	23 dBm		
Sendeeffekt (FCC)	27 dBm		
Driftsmodus	Infrastruktur-tilstand		
		Logistik data	
		Harmoniseret systemkode (HS)	85176990



6935364052867

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-OCT-2024. Prints or copies of Information are only valid on the printed Publication date